

Features


- Low Insertion Loss
- Wide Passband
- High Channel Isolation
- High Stability and reliability
- Epoxy free on optical path
- Compact size

Applications

- Line Monitoring
- WDM Network
- Telecommunication
- Cellular Application
- Fiber Optical Amplifier
- Access Network

Specification:

Parameters		Specification
Operating Wavelength (nm)		1310~1610
Channel (nm)		1270,1290,1310,1330,1350,1370,1390,1410,1430,1450,1470,1490,1510,1530,1550,1570,
Channel Spacing (nm)		20
Channel Passband(@-0.5dB bandwidth) (nm)		±6.5
Insertion Loss ¹ (dB)	1270~1570	≤2.5
Isolation (dB)	Adjacent	≥30
	Non-adjacent	≥40
Insertion Loss Temperature Sensitivity (dB)		<0.5
Wavelength Temperature Shifting (nm/°C)		<0.002
Polarization Dependent Loss (dB)		≤0.15
Polarization Mode Dispersion (ps)		≤0.2
Directivity (dB)		>50
Ripple (dB)		≤0.5
Return Loss (dB)		>45
Maximum Power Handing (mW)		300
Storage Temperature (°C)		-10~+75



Storage Temperature (°C)	-40~+85
Fiber Type	900um ,G657A1
Fiber Length	0.25±0.02 (包含连接头)
Package size (mm)	L50×W50×H6.2

Notes: 1. Insertion Loss tested with connector.

 **Order Information: HC-16CH-MINI CWDM-A-B-C-D-E**

Number of Channels	1st Channel	Configuration	Fiber Type	Fiber Length	Connector
	A	B	C	D	E
16 Channel	27=1270nm 47=1470nm 61=1610nm	M=Mux D=Demux	1=Bare fiber 2=900um loose tube 3=2mm Cable 4=3mm Cable	1=1m 2=2m S=Specify	0=None 1=SC/APC 2=SC/PC 3=LC S=Specify