



## 技术参数

Parameter/参数		Value
Connector Type		FC/UPC, SC/UPC, LC/UPC FC/APC, SC/APC,
Wavelength (nm)		1310 , 1550
Insertion Loss (dB)		≤0.3
Return loss(dB)	UPC Type	≥50
	APC type	≥60
Extinction Ratio 23°C (dB)		≥23
Fiber Type		PM1310, PM1550
Key Orientation		Slow Axis
Angle (deg)		±3
Operating temperature (°C)		-5 ~ +70
Storage temperature (°C)		-40 ~ +80

 **订购信息 : HC-PMJP-A-B-C-D-E**

<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>
<b>Wavelength</b>	<b>Pigtail Type</b>	<b>Fiber Length</b>	<b>Connector1</b>	<b>Connector2</b>
1=850nm	1=250um bare fiber	H=0.5m	0=None	0=None
2=980nm	2=900um loose tube	8=0.8m	1=FC/UPC	1=FC/UPC
3=1064nm	3=3mm loose tube	1=1.0m	2=FC/APC	2=FC/APC
4=1310nm	4=2mm loose tube	2=2.0m	3=SC/APC	3=SC/APC
5=1480nm		3=3.0m	4=SC/UPC	4=SC/UPC
6=1550nm		4=4.0m	5=MU	5=MU
		5=5.0m	6=LC/PC	6=LC/PC
		A=0.3m	7=LC/APC	7=LC/APC
		B=1.5m	8=E2000 APC	8=E2000 APC
			9=E2000 PC	9=E2000 PC